



# EW30 ATW

## Product Specification





## Machine Technical Details

TECHNICAL FEATURES - EW 30	
<b>WATER PRODUCTION</b>	30 litres/day (at 24°C and 55% Relative Humidity)
<b>WORKING CONDITIONS</b>	Temp range 18-40°C / Relative Humidity range = 25-100%
<b>UNIT FRAME</b>	Zinc Passivate Mild Steel – powder coated
<b>TANK</b>	Sealed stainless steel S316 - 20 litre
<b>TANK LEVEL SENSOR</b>	Multi level sensor
<b>WASTE-WATER - DRAIN TANK</b>	4 litre auto sensor
<b>SIZE / WEIGHT (GENERATOR)</b>	H 1116 mm x W 505 mm x L 587 mm / 114 kg
<b>PURIFICATION</b>	UVC, 5 stage water filtration & mineralization, recirculation system, anti bacterial air filter
<b>REFRIGERATING GAS (AIR TREATMENT)</b>	R-410a
<b>ELECTRICAL SUPPLY</b>	220v 50Hz – single phase
<b>REQUIRED ELECTRICAL POWER SOURCE CONNECTION SOCKET</b>	13 Amp Standard household socket
<b>POWER CONSUMPTION</b>	0.8 Kw
<b>NOISE</b>	Less than 60 dB
<b>WATER CHILLER CAPABILITY</b>	10-12°C at dispenser at indoor ambient
<b>HIGH TECH ACOUSTIC INSULATION</b>	DbA noise reduction
<b>WATER QUALITY &amp; CERT STANDARDS</b>	WHO, GSO149, CE, CB, ECAS, Halal
<b>MANUFACTURING PROCESS</b>	ISO9001:2015
<b>COLOUR</b>	Various / custom image branding

